

Q1
a set of brushes having a backplate and brush bristles,
said set of brushes residing in said recessed groove,
protruding out from said main body member and extending
past [the] a gap for preventing an object from being
entrapped in the gap; and

said brush bristles having a length being increased up to
a desired length for covering the gap, as seen along said
back plate.

Cancel claim 2.

Claim 3, line 2, change "claim 2" to --claim 1--.

Claim 4, line 2, change "claim 2" to --claim 1--.

Cancel claim 5.

Q2
Claim ⁵~~6~~ (amended). [The passenger conveyor safety
apparatus according to claim 1, including] In an
escalator or a moving sidewalk having a skirt panel and, a
step or a walk path, defining a gap between the skirt
panel and the step or the walk path, a passenger conveyor
safety apparatus comprising:

G2
a main body member having a recessed groove formed
therein;

a set of brushes residing in said recessed groove,
protruding out from said main body member and extending
past the gap for preventing an object from being entrapped
in the gap; and

a set of hinged locking members connected at both ends of
said recessed groove on said main body member for locking
and releasing said set of brushes in said recessed groove.

A3
Claim ~~8~~¹⁶ (amended). [The passenger conveyor safety
apparatus according to claim 1, including] In an
escalator or a moving sidewalk having a skirt panel and, a
step or a walk path, defining a gap between the skirt
panel and the step or the walk path, a passenger conveyor
safety apparatus comprising:

a main body member having a recessed groove formed
therein;

a set of brushes residing in said recessed groove,
protruding out from said main body member and extending
past the gap for preventing an object from being entrapped
in the gap; and